Development System Providing Information for Pest Control and Growth Management of Apple Based on ICT

J. W. So^{1*}, Y. K. Han¹, S. K. Kim¹, J. S. Park¹, S. M. Yoon¹, J. S. Lee¹, M. I. Ahn^{1,2},

and E. W. Park³

¹R&D Center, EPINET Co., Ltd, Anyang 14056, Korea

²Department of Biomedical Science, Sun Moon University, Asan 31460, Korea, ³Department of Agricultural Biotechnology, Seoul National University, Seoul 08826, Korea

I. Introduction

Recently, Korea is pursuing the convergence of ICT with agriculture as a core strategy to resolve the rising production costs incurred by the lack of agriculture labor, aging and energy cost increase, and to revitalize the stagnant agricultural industry. To date, Korean ICT-based research in the field of agriculture has been active in the areas of sensing technology, protected cultivation automation control system and plant factory. Yet, there have not been many cases applying ICT to outdoor field crops.

In this study, an ICT-based web system was developed by converging agriculture and IT technology to provide information to support the precise management of apples. Here, a weather and disaster alert and an apple growth estimation system were created via ICT-based environmental measurement, and a web-mobile user interface was implemented to enable users to access information through the web or a smartphone. In terms of function, the system broadly consists of a pest outbreak system, an apple growth estimation system, and an irrigation control system utilizing environmental measurement information. A brief introduction shall be made in the following text.

II. Materials and Methods

2.1. System outline

The system developed by this research team collects real-time environmental measurements within a group of apple trees, including temperature, relative humidity, rain, and soil moisture, by utilizing the unmanned weather observation equipment installed in each group. The collected data is used in a temperature-based degree day model of *Phyllonorycter ringoniella*, *Grapholita molesta* and *Carposina niponensis*, to predict their growth stages and provide the

^{*} Correspondence to : ahnmi@epinet.kr

information required for pest control. Also, by predicting and providing information on the growth stages of the apples, the system supports proper crop management in the sprouting and full bloom stages. Finally, by utilizing the environmental measurements observed in the orchard, the system estimates the evapotranspiration in the orchard and provides automated remote control of irrigation according to a base value set by an expert.



Fig. 1. Overview system providing information for pest control and growth management of apple based on ICT.

2.2. Forecasting pest outbreaks using environmental measurements

Predictions about *Phyllonorycter ringoniella*, *Grapholita molesta* and *Carposina niponensis* were made using the reported model. Models for the target pests were all developed based on the temperature-based degree day model, and these were then modularized into a programming language and uploaded to the system. The model operates on a daily basis, and not only uses real-time weather information but also utilizes the local and medium-range forecasts of the Korea Meteorological Administration (KMA) to provide up to 10 days of pest forecasts.

2.3. Apple growth estimation using environmental measurements

The estimated sprouting date and full bloom date are provided by utilizing the observed data and average annual climate data for the group of trees. The growth estimation model for the sprouting and full bloom of apples was based on the reported base temperature of 6.1° C, the chilling requirement of -100.5 days, and the full bloom heat requirement of 275.1 days (Kim *et al.*, 2009).

2.4. Irrigation Control System using Environmental Measurements

Automatic irrigation is executed according to the automated irrigation system, as shown in Fig. 3. The estimated value of actual evapotranspiration is deduced by applying the crop coefficient by growth stage to the observed data in the orchard and the potential evapotranspiration obtained from the formula in Fig. 2. Irrigation hours per day is deduced by adjusting the actual evapotranspiration based on the expert's set value (number of drip irrigation units, volume per hour) and observed rainfall values. The auto irrigation system using observed soil moisture is controlled by the hour according to the settings for the period or minimum value.

$$ETO = \frac{(0.408 \times asc \times Rn) + r \times \left(\frac{900.0}{T + 273.0}\right) \times PV \times \left(Es - \left(\frac{Es_Ea}{10.0}\right)\right)}{(asc + r \times (1.0 + 0.34 \times PV))}$$

Fig. 2. Formula for calculating potential evapotranspiration.

ETO=soil moisture, r=moisture coefficient, T=average temperature, PV=average wind velocity, Es=saturated water vapor pressure, rad=solar irradiance, Es_Ea=saturation deficit, asc=slope



Fig. 3. Flow chart for the automated irrigation control system.

III. Results and Discussion

3.1. Forecasting pest outbreaks using environmental measurements

Fig. 4 is a screenshot of the calendar-based user interface showing predictions for *Phyllonorycter ringoniella*, *Grapholita molesta* and *Carposina niponensis* based on environmental measurements. When the user inserts research findings for a registered time period on his/her account, a blue mark appears in the calendar. This is to provide support for more efficient pest control decision-making based on the pest prediction data and the density of pests observed in the field.

A module estimating pest appearance density through image sensing, which is under research, will be added. Also, if the expert's stage-by-stage algorithm for pest control decision-making is applied, it is expected to serve as the major expert pest control system for apples.



Fig. 4. A screenshot showing ICT-based prediction of pest outbreak and IT trap data.

3.2. Apple growth estimation using environmental measurements

Fig. 5 demonstrates a prediction of growth period and possible damage from low temperature in calendar form, by utilizing environmental measurements and the KMA's forecasts. The growth period (sprouting and full bloom date) is shown after running the March model of each year, and the prediction of low temperature damage is shown up to 10 days from the present date. Such information is expected to assist the user establish scheduled plans for preparation and implementation of soil amendment, artificial pollination, and low temperature damage mitigation technology.

	ICT기반사과원 정말관리 시스템						ICT 기반 사과원 정밀관리 시스템						
				안문일님	👌 회원정보수정	O LOGOUT	3					🔺 회원정보수정	O LOGOL
	·작과학원사과인		[16일(화)				ICT과제/국립원예목			16일(화)			
생육시/	/기상위험	1					> 생육시기	1/기상위험	1				
생육시기 확인					■생육시	기 📕 예측	생육시기 확인					■생육시	기 📕예측
난달		20	16년 3월			다음달	지난달		201	.6 <mark>년 4</mark> 월			다음달
일	월	화	수	목	금	토	일	5 0	화	수	목	금	토
		1	2	3	4	5						1	
6	7	8	9 M E	10 - II 0	11	12	3	4	5	6	7	8	1
13 피해	14	15 은피해	16	17	18	19	10	11	12	13	14	15 19	1 개일
20	21 아일	22	23	24	25	26	17	18	19	20	21	22	2
27	28	29	30	31			24	25	26	27	28	29	3
생육시기는 해당 (편도의 3월 에 계산	됩니다.					※생육시기는 해당 일	년도의 3월 에 계산	됩니다.				

Fig. 5. Screenshots of ICT-based apple growth prediction and meteorological risks.

3.3. Irrigation control system using environmental measurements

Fig. 6 is a screenshot of the table-based user interface showing environmental measurements and the potential and actual evapotranspiration deduced from these measurements. The user can access the information for any given time period, and can also download an Excel file containing this information. When the user turns on auto irrigation, a table-based user interface provides the operation history, including evapotranspiration and soil moisture, in the "automation history" section. By viewing the operation history and irrigation timing, the user can check the irrigation volume in the past. It is expected that the user will be able utilize such information when making agricultural decisions.

관측 연설·단운·로드 관측·단운·토르 응발산 제아 설정 2016-08-16 0 0 27.7. 75 3.1. 2016-08-15 1.08 1.1 50 28.9 70 0.4	응여부 사용여부		- 201 - 201						▶ 관수 자동 설정	
····································	····································		100 100 2010 100 11 -							자동 제어
관측일 실체증발산량(mm) 흥발산평(mm) 관수시간(성) 평균기온(C) 평균습도(%) 양누정감우정 >증발산 제어 설정 2016-08-15 0 0 27.7 7.5 3.1. 201-09-15 1.08 1.1 50 28.9 70 0.4 21	학실각운곳으 환신성(mm) 환신시간(約) 형고 신간(2) 형고 신조(2) 형고 신조(2) 영고 신조(2) 정고 신조(2) 전고 신조(2) <td>2016</td> <td>/08/09 - 2016/08/16</td> <td></td> <td>검색</td> <td></td> <td></td> <td></td> <td>사용여부 사용함</td> <td>토양수분 사용안함 증발산 사용함</td>	2016	/08/09 - 2016/08/16		검색				사용여부 사용함	토양수분 사용안함 증발산 사용함
관측일 실체증발상량(mm) 출발상량(mm) 관수사간(法) 평균기운(*C) 평균급도(*M) 일두적감우 전) 등발산 제어 설정 2016-08-15 0 0 27.7 75 3.1 22 24	환상연nm 환수시간(約 형고 오(2) 형고수값(2) 형고 요(2) 영고수값(2) 형고 요(2) 영고수값(2) 승고 요(2) 승규 요(2)							1		
관측일 실제증발상명(mm) 증발상명(mm) 관수시간(방 평균기운(C) 평균수도(%) 일두적간위장 수 22 · · · · · · · · · · · · · · · · ·	환성 (mm) 한 수시간(m) 형고 (200) 형고 (200) 형고 (200) 철고 (200) 월고 (200)									
2016-08-16 0 0 27.7 75 3.1 22 2016-08-15 1.08 1.1 50 28.9 70 0.4 22	Action Action<								> 증발산 제어 설정	
2016-08-15 0 0 0 27.7 75 3.1 22 2016-08-15 1.08 1.1 50 28.9 70 0.4	0 0 27.7 75 3.1 .08 1.1 50 28.9 70 0.4 .66 1.69 49 29.5 69 0 .61 1.65 37 29.8 66 0	관측일	실제증발산량(mm)	증발산량(mm)	관수시간(분)	평균기온(°C)	평균습도(%)	일누적강우량	저전과스 개스	
2016-08-15 1.08 1.1 50 28.9 70 0.4	.08 1.1 50 28.9 70 0.4 .66 1.69 49 29.5 69 0 .61 1.65 37 29.8 66 0 4255 .61 .61 .61 .61 .61 .61 .61 .61	2016-08-16	0	0	0	27.7	75	3.1		
	1.69 1.69 1.69 29.5 69 0 23 .61 1.65 37 29.8 66 0 실정등록	2016-08-15	1.08	1.1	50	28.9	70	0.4	시간다 유량(리터/개)	
2016-08-14 1.66 1.69 49 29.5 69 0	설정등록	2016-08-14	1.66	1.69	49	29.5	69	0		
2016-08-13 1.61 1.65 37 29.8 66 0 설정등록	L2 1.23 44 29.7 68 0	2016-08-13	1.61	1.65	37	29.8	66	0		설정등록
2016-08-12 1.2 1.23 44 29.7 68 0		2016-08-12	1.2	1.23	44	29.7	68	0		
2016-08-11 1.46 1.49 37 29.4 70 0	.46 1.49 37 2.9.4 70 0	2016-08-11	1.46	1.49	37	29.4	70	0		
		2016-08-10	1.21	1.23	0	28.4	72	0		
2016-08-10 1.21 1.23 0 28.4 72 0	.21 1.23 0 28.4 72 0	2016-08-09	0.99	1.01	0	27.5	75	1.1		
		016-08-10	1.21	1.23	0	28.4	72	0		
2016-08-10 1.21 1.23 0 28.4 72 0	21 1.23 0 28.4 72 0	2016-08-09	0.99	1.01	0	27.5	75	1.1		

Fig. 6. Screenshots of evapotranspiration predictions using ICT-based environmental measurements, and the irrigation control system that utilizes these predictions.

Acknowledgements

This work was carried out with the support of "Technology Development for Pest Control and Growth Management of Apple based on ICT (Project No.PJ010538042016)" Rural Development Administration, Republic of Korea.

References

Kim, S. O., U. Chung, S. H. Kim, I. M. Choi, and J. I. Yun, 2009: The suitable region and site for 'Fuji' apple under the projected climate in South Korea. *Korean Journal of Agricultural and Forest Meteorology* **11**(4), 162-173